

BACKLIGHT SYSTEM AND LIGHT GUIDE PLATE USED THEREIN

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to a backlight system, and particularly to a backlight system used for a liquid crystal display (LCD).

2. Description of Related Art

[0002] In an LCD, because liquid crystal is not a luminous element but is instead a control element regulating passage of light therethrough, a light source is needed. In most cases, the light source is combined with some other apparatus to become an integrated system that is called a backlight system or a front light system according to a direction of the light emitted.

[0003] Referring to Fig. 6, an LCD assembly 100 comprises an LCD panel 101 and a backlight system 102. The backlight system 102 comprises a light source 1021, a light source cover 1022, a reflection plate 1023, a light guide plate 1024 and a reflection polarizer 1025. The light emitted from the light source 1021 enters into the light guide plate 1024 directly, or indirectly by being reflected by the light source cover 1022. The reflection plate 1023 disposed under the light guide plate 1024 reflects light coming from the light guide plate 1024 back into the light guide plate 1024. Outgoing light from the light guide plate 1024 to the reflection polarizer 1025 is composed of different components of polarized lights, i.e., P polarized light and S polarized light. The two polarized light components' polarization axes are perpendicular to each other. The S polarized light has proper

polarization and passes through the reflection polarizer 1025 and is used to illuminate the LCD panel 101. The P polarized light is reflected by the reflection polarizer 1025 and reenter the light guide plate 1024. Reflected again by the reflection plate 1023, the P polarized light is turned into a common light which can be seen as a combination of P polarized light and S polarized light as before, but just with a lower intensity. This common light is then directed to the reflection polarizer 1025 and is partly passed and partly reflected back. The process repeats again and again, so the P polarized light reflected by the reflection polarizer 1025 is reused.

[0004] Although the P polarized light reflected by the reflection polarizer 1025 is reused, much of it is lost in the process. This is because, when the P light is reflected by the reflection polarizer 1025 to enter into the light guide plate 1024, part of the P polarized light is absorbed by the light guide plate 1024; the residual light then will also lose a little strength when reflected by the reflection plate 1023. In the whole recycling process, the loss can not be neglected.

[0005] At the same time, the backlight system does not use a diffusing plate or other apparatus having a similar function to scatter the light. This causes an unevenness of the light emitted from the reflection polarizer 1025, so an illumination to the LCD panel 101 is not satisfying.

[0006] Referring to FIG. 7, U.S Pat.No.6,448,955, issued Sep. 10, 2002, discloses an LCD assembly 200, which comprises a liquid crystal panel 201 and a backlight system 202. The liquid crystal panel 201 comprises a first plate 2011, a liquid crystal layer 2012 and a second plate 2013. The backlight system 202 comprises two light sources 2021, two corresponding light source covers 2022, two

corresponding light guide plates 2024, a reflection plate 2023, a diffusion plate 2025, a brightness enhancing film 2026, a reflection polarizer 2027 and a special cover layer 2028.

[0007] In operation, The light emitted from the two light sources 2021 enters into the two light guide plates 2024 directly or indirectly after being reflected by the light source cover 2022. With the reflection plate 2023 disposed under the two light guide plates 2024, the outgoing light from the two light guide plates 2024 is directed to the diffusion plate 2025. Then the diffused light enters into brightness enhancing film 2026. The incident light at the reflection polarizer 2027 can be seen as a combination of two parts, i.e., the P polarized light and the S polarized light and their polarization axes are perpendicular to each other. Having the proper polarization, the S light passes the reflection polarizer 2027 and is used to illuminate the LCD layer 2012; and the P light is reflected by the reflection polarizer 2027 to enter the light guide plate 2024 through the brightness enhance film 2026 and the diffusion plate 2025. Reflected by the reflection plate 2023, the P light is turned into common light which can be seen as a combination of P light and S light, as before, but with a lower intensity. This common light is then directed to the reflection polarizer 2027 and is partly passed, and is partly reflected back. This process repeats again and again, so the P light reflected by the reflection polarizer 2027 is reused.

[0008] The addition of the diffusion plate 2025 makes the final light more uniform; the using of the brightness enhancing film 2026 enhances the utilization efficiency of the light. But there is still one problem unsolved. When the P light is reflected by the reflection polarizer 2027 to enter the light guide plates 2024, part

of the P light is absorbed by the light guide plates 2024; the residual light then will lose a little intensity when it is reflected by the reflection plate 2023. Remembering that there is a diffusion plate 2025 added to the system, so in the whole process, the loss due to absorbance and reflection will amount to a quite large percentage.

[0009] It is desirable to provide a backlight system and a light guide plate used therein which overcomes the above problems.

SUMMARY OF THE INVENTION

[0007] An object of the present invention is to provide a backlight system that provides a uniform and more intense light, and consumes less power.

[0008] A backlight system of present invention comprises a light source, a light guide plate, a reflection plate, a diffusion plate and a reflection polarizer. The light source is disposed at one side of the light guide plate. The reflection plate, the light guide plate, the diffusion plate and the reflection polarizer are stacked one up the other. A plurality of prisms are disposed on a surface of the diffusion plate, which forms a plurality of V-shaped grooves. The reflection polarizer lets light polarized in one certain direction which will be called the S light, pass, and reflects light polarized, in a direction perpendicular to the said certain direction, which light will be called the P light.

[0009] The prisms can function as light conversion elements to turn the P light reflected by the reflection polarizer to common light which can be seen as a combination of the P light and the S light. So the process of conversion is much simplified since only one reflection is used. The relatively large absorbance losses in the light guide plate, as the prior art, is avoided, and the utilization efficiency of

the light is enhanced.

[0010] Other objects, advantages, and novel features of the present invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Fig. 1 is a side view of a first embodiment of a backlight system according to the present invention;

[0012] Fig. 2 is an optical paths schematic view of the backlight system in Fig. 1;

[0013] Fig. 3 is a perspective view of prisms on a diffusion plate of the backlight system according to the present invention;

[0014] Fig. 4 is a perspective view of another form of prisms on the diffusion plate of a backlight system according to the present invention;

[0015] Fig. 5 is a side view of a second embodiment of a backlight system according to the present invention;

[0016] Fig. 6 is a cross-sectional view of a conventional liquid crystal display assembly;

[0017] Fig. 7 is a cross-sectional view of another conventional liquid crystal display assembly;

[0018] Fig. 8 is an optical paths schematic view of the liquid crystal display module in Fig. 7;

DETAILED DESCRIPTION OF THE INVENTION

[0019] Referring to Fig. 1, a first embodiment of a backlight system 300 according to the present invention comprises a light source 3021, a light source cover 3022, a reflection plate 3023, a light guide plate 3024, a diffusion plate 3025 and a reflection polarizer 3027. The light source 3021 is disposed at one side of the light guide plate 3024 and is surrounded by the light source cover 3022 on three sides. The reflection plate 3023, the light guide plate 3024, the diffusion plate 3025 and the reflection polarizer 3027 are stacked up one on top of the other. A plurality of prisms 11 (see FIG. 3) are disposed on a surface of the diffusion plate 3025, which forms a plurality of V-shaped grooves (not labeled).

[0020] Referring to Fig. 2, the light emitted from the light source 3021 enters into the light guide plate 3024 directly, or indirectly by being reflected by the light source cover 3022. With the reflection plate 3023 disposed under the light guide plate 3024, the light emitted from the two light guide plate 3024 is directed to the diffusion plate 3025. The diffused incident light at the reflection polarizer 3027 can be seen as a combination of two parts, i.e., a P polarized light and an S polarized light and their polarization axes are perpendicular to each other. Having a proper polarization state, the S polarized light passes the reflection polarizer 3027 and the P polarized light is reflected back by the reflection polarizer 3027 to the diffusion plate 3025. Reflected by the V-shaped grooves formed by the prisms 11 on the diffusion plate 3025, the P light is turned to common light, which can be seen as the combination of the P polarized light and the S polarized light as before, but just with a lower intensity. This common light is then directed to the reflection polarizer 3027 and is partly passed, and is partly reflected back. This process

repeats again and again, so the P polarized light reflected by the reflection polarizer 3027 is reused.

[0021] The plurality of prisms 11 form V-shaped grooves, which serve as light conversion elements to turn P polarized light to common light only by reflection action. Unlike the prior art, there is no light guide plate or diffusion plate in the light path, so the conversion process generates only loss by reflection, the loss caused by the absorption in the light guide plate or diffusion plate of the light is obviated. Consequently, the utilization efficiency of the light is increased.

[0022] Referring to Fig. 3, the plurality of prisms 11 are disposed parallel on a surface of the diffusion plate 3025 at equal intervals, which forms a plurality of V-shaped grooves(not labeled).

[0023] Referring to Fig. 4, a plurality of pyramid-shaped prisms 12 are disposed evenly on a surface of the diffusion plate 3025, which forms V-shaped parallel grooves in two perpendicular directions on a surface of the diffusion plate 3025.

[0024] Referring to Fig. 5, a second embodiment of a backlight system 400 according to the present invention comprises a light source 4021, a light source cover 4022, a wedge shaped light guide plate 4024, a reflection film 4023 formed on the light guide plate 4024, a diffusion plate 4025, a brightness enhancing film 4026 and a reflection polarizer 4027. The light source 4021 is disposed at a wider side of the light guide plate 4024 and is surrounded by the light source cover 4022 on three sides. The reflection film 4023, the light guide plate 4024, the diffusion plate 4025, the brightness enhancing film 4026 and the reflection polarizer 4027 are stacked up one on top of another. The V-shaped grooves formed by the prisms 2

on the light diffusion plate 4025 are a light conversion element which has a same function as in the first embodiment.

[0025] The differences between the first and second embodiments comprise three points. The first is the usage of the wedge shaped light guide plate 4024 instead of the flat plate; the second is the reflection film 4023 being formed on the light guide plate 4024 as a substitute for the reflection plate 3023; the third is the addition of the brightness enhancing plate 4026 between the diffusion plate 4025 and the reflection polarizer 4027.

[0026] Accomplishing the light conversion with the grooves formed by the prisms 2, the second embodiment also avoids the light absorption by the light guide plate or the light diffusion plate in prior art. Compared with the first embodiment, the wedge-shaped light guide plate and the reflection film of the second embodiment altogether allow the backlight system to occupy less space while retaining or even enhancing the reflection effect, because the wedge shape of the light guide plate can result in a more uniform reflection. The addition of the brightness enhancing plate could enhance the utilization efficiency of the light while only requiring a little larger volume. So the second embodiment provides a higher intensity light and occupies less space. It could be applied to high end products, to which performance is considered relatively more important than price.

[0027] It is to be understood, however, that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles

of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.